

SERVICE SPECIFICATIONS

SERVICE DATA

E00X8-01

| | | |
|--------------|---|---|
| Turbocharger | Turbocharging pressure | 49 – 81 kPa (0.50 – 0.83 kgf/cm ² , 7.1 – 11.8 psi) |
| | Impeller wheel axial play Impeller wheel radial play | 0.13 mm (0.0051 in.) or less 0.18 mm (0.0071 in.) or less |

TORQUE SPECIFICATIONS

E00X8-01

| Part tightened | N-m | kgf-cm | ft-lbf |
|---|-----------|--------|-----------|
| Turbine outlet elbow x Turbocharger | 64 | 650 | 47 |
| Side bearing housing plate x Turbocharger | 11 | 120 | 9 |
| Turbo water pipe x Turbocharger | 11 | 120 | 9 |
| Turbocharger x Exhaust manifold | 64 | 650 | 47 |
| Oil pipe x Turbocharger | 17 | 175 | 13 |
| Oil pipe x Cylinder block (Bolt) | 43 | 440 | 32 |
| Oil pipe x Cylinder block (Union bolt) | 51 | 525 | 38 |
| Turbocharger stay x Turbocharger | 69 | 705 | 51 |
| Turbocharger stay x Cylinder block | 59 | 600 | 43 |
| Oxygen sensor x Turbine outlet elbow | 44 | 450 | 33 |
| No.4 air tube stay x Cylinder head | 19 | 195 | 14 |
| No.4 air tube stay x No.4 air tube | 19 | 195 | 14 |
| Air by-pass valve x No.4 air tube | 19 | 195 | 14 |
| Main TWC x Turbine outlet elbow | 29 | 300 | 22 |
| TWC stay x Main TWC | 59 | 600 | 43 |
| TWC stay x Cylinder block | 59 | 600 | 43 |
| Clutch release cylinder x Transaxle | 12 | 120 | 9 |
| Front engine mounting bracket x Transaxle | 77 | 790 | 57 |
| Front engine mounting insulator x Body | 77 | 790 | 57 |
| Front engine mounting insulator x Bracket | 96 | 980 | 71 |
| Front exhaust pipe x Main TWC | 62 | 630 | 46 |
| Front exhaust pipe support bracket x Suspension crossmember | 21 | 210 | 15 |
| Suspension member damper x Suspension crossmember | 21 | 210 | 15 |
| Tailpipe x Body bracket | 66 | 670 | 48 |
| Tailpipe x Front exhaust pipe | 43 | 440 | 32 |
| Tailpipe bracket x Front exhaust pipe bracket | 19 | 190 | 14 |
| A/C idler pulley bracket x Cylinder block (12 mm head) | 25 | 250 | 18 |
| A/C idler pulley bracket x Cylinder block (14 mm head) | 27 | 275 | 20 |
| A/C idler pulley bracket x RH engine hanger | 37 | 375 | 27 |
| A/C compressor x Cylinder block | 25 | 250 | 18 |
| Lower suspension brace x Body | 73 | 740 | 54 |