

SERVICE SPECIFICATIONS

8200P-01

SERVICE DATA

vsv (for EGR)	Resistance (at 20° C (68° F))	33 -39Ω
---------------	-------------------------------	---------

TORQUE SPECIFICATIONS

8200Q-01

Part tightened	N-m	kgf-cm	ft-lbf
TVS x Water outlet housing	29	300	22
EGR valve x Intake manifold	19	195	19
EGR valve x EGR pipe	59	600	43
Main TWC x Turbine outlet elbow	29	300	22
TWC stay x Main TWC	59	600	43
TWC stay x Cylinder block	59	600	43
Clutch release cylinder x Transaxle	12	120	9
Front engine mounting bracket x Transaxle	77	790	57
Front engine mounting insulator x Body	77	790	57
Front engine mounting insulator x Bracket	96	980	71
Front exhaust pipe x Main TWC	62	630	46
Front exhaust pipe support bracket x Suspension crossmember	21	210	15
Suspension member damper x Suspension crossmember	21	210	15
Tailpipe x Body bracket	66	670	48
Tailpipe x Front exhaust pipe	43	440	32
Tailpipe bracket x Front exhaust pipe bracket	19	190	14
A/C idler pulley bracket x Cylinder block (12 mm head)	25	250	18
A/C idler pulley bracket x Cylinder block (14 mm head)	27	275	20
A/C idler pulley bracket x RH engine hanger	37	375	27
A/C compressor x Cylinder block	25	250	18
Lower suspension brace x Body	73	740	54